

# Dryflow **D-Flow Eco**

A low noise powerhouse that radiates style and elegance




high traffic



- Robust & durable ●
- Low noise ●
- Fault and service notification ●
- Internal on / off heater ●
- Biocote® anti bacterial coating ●
- Can be fitted direct to waste pipe ●
- Water collection system ●
- Adjustable motor speed ●
- HEPA filter ●

**For life.**  
FREE REPAIRS FOR LIFE

**Carbon neutral**  
Product  
ClimatePartner.com/16672-2202-1001



Dries possible per £1	2,857
Electrical Supply Voltage	220 - 240 V
Electrical Supply Frequency	50/60 Hz
Expected Motor Life	3000 Hours
Rated Power	0.42 kW - 1.5kW
Approx. Watt-Hours per Dry	1.75 - 4.17 Wh (Internal on / off heater switch & adjustable motor speed)
Heater Element Power	0.4 kW
Operating Sound Level	62 - 72 dB
Motor Speed	32,000 RPM
Air Speed	260 MPH

Operating Temperature Range	At ambient temp (21°C) - 33°C
Motor Cut off Time	30 seconds
Motor Class	Class I
Materials	ABS
Weight	8.3 kg
Finishes Available & Codes	Silver (DF01G), White (DF01W), Black (DF01B)
IP Rating	IPX4
Cable Entry Point	Rear, with access available from bottom
Certifications and Awards	CE, CB, EMC, EAC, GS, UL, ROHS, G-Mark, Building Green